

# Product data sheet

GUSTAV I (W. SHIELD ON SIDE FACING BUILDING)  
9.681.3046.27  
LEIPZIGER LEUCHTEN




Mounting height of 3.00 to 4.50 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge - Order pole, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	50 W	LOR	50%
Lamp flux	2000 lm	ULOR	10%
Luminous efficacy	17 lm/W	Total flux	991 lm
CCT	3400 K	Total power	59 W
CRI	54		



### 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	50%
Lamp flux	4000 lm	ULOR	10%
Luminous efficacy	22 lm/W	Total flux	1982 lm
CCT	3400 K	Total power	89 W
CRI	54		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 29.13 in  
Diameter: 9.84 in

## Electric

System power: 59-89 W

## Protection

IP: 55