## Product data sheet


LUCAS XI (1-ARMED) 9.849.2152.15 LEIPZIGER LEUCHTEN






Mounting height 6.00 m. Other heights please inquire. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes reinforced and hot-galvanized triple offset Pole dia. 76 mm inclusive painted bracket made of spezial steel Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



50 W	LOR	84%
3500 lm	Total flux	2932 lm
47 lm/W	Total power	62 W
2000 K		
25		
	3500 lm 47 lm/W 2000 K	3500 lmTotal flux47 lm/WTotal power2000 K



1 x Hiah	pressure	sodium	vanour	lamn
т х піўн	pressure	soulum	vapour	iamp

0.			
Nominal lamp power	70 W	LOR	84%
Lamp flux	5600 lm	Total flux	4691 lm
Luminous efficacy	57 lm/W	Total power	83 W
CCT	2000 K		
CRI	25		

Mounting mode	Electric
Pole top mounted	System power: 62-83 W
Shape and measurements	Protection
Height: 19.69 in	IP: 55
Diameter: 22.44 in	