

Product data sheet


KORA PIII (POLLERLEUCHTE EINSEITIG)
9.822.5407.00
LEIPZIGER LEUCHTEN



IP
65

Bollard- particularly (designed or constructed or built) in order to give orientation and light to entrances and ways in parks and gardens. - Light exit: Kora P I and P II on 4 sides Kora P III on 1 or 3 sides - Impact-resistant opal polycarbonate cube, UV-stabilized - Special steel luminaire body and unit carrier, available painted in DB 703 (Iron Glimmer) or in any RAL or DB colour without surcharge, or ground and passivated - Adapter jack connection - Luminaire body completely detachable for lamp replacement, opens with tool - Kora P I with open incl. cable joint box for 2 cables 5 x 10 mm² or cables 5 x 6 mm² Voltage: 230V 50Hz Protected to: IP 65 Protection class: I/II Made to DIN VDE 0711

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	55 W	LOR	8%
Lamp flux	4800 lm	ULOR	4%
Luminous efficacy	6 lm/W	Total flux	380 lm
CCT	2899 K	Total power	61 W
CRI	90		

Mounting mode

Standing / Bollard

Electric

System power: 61 W

Shape and measurements

Length: 4.72 in

Width: 4.72 in

Height: 35.43 in

Protection

IP: 65