


Product data sheet

WAN DOWNLIGHT
03.6151/QT-12/20W/35W/50W
FLOS




Ceiling recessed lighting providing direct light. Aluminium body. Provide by two different ring due to fix the safety tempered glass, in shiny black and enameled green.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gy6.35
Lamp flux	910 lm	LOR	41%
Luminous efficacy	7 lm/W	Total flux	375 lm
CCT	3000 K	Total power	50 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	35 W	Socket	Gy6.35
Lamp flux	600 lm	LOR	41%
Luminous efficacy	7 lm/W	Total flux	247 lm
CCT	3000 K	Total power	35 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	20 W	Socket	E27
Lamp flux	300 lm	LOR	41%
Luminous efficacy	6 lm/W	Total flux	124 lm
CCT	2756 K	Total power	22 W
CRI	99		

Mounting mode

Ceiling mounted

Electric

System power: 22-50 W
Appliance Class: II

Shape and measurements

Length: 4.45 in

Width: 4.45 in

Height: 3.54 in

Adjustability

Fixed

Protection

IP: 20