

Product data sheet


MAXI MELRIE
486121
FLOS



IP
65

• Outdoor luminaire for surface installation on wall • Configuration: polycarbonate structure and die-cast aluminium cover, diecast aluminium base (MaxiMelrie) EN AB-47100 alloy (low copper content). • Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Expanded silicone gaskets.

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	26 W	Socket	G24Q-2
Lamp flux	1800 lm	LOR	13%
Luminous efficacy	9 lm/W	Total flux	231 lm
CCT	3000 K	Total power	26 W
CRI	84		

Mounting mode

Wall mounted

Electric

System power: 26 W

Shape and measurements

Length: 11.02 in

Width: 5.51 in

Height: 4.72 in

Protection

IP: 65

Adjustability

Fixed