Product data sheet

EVA II 9.898.3142.05

LEIPZIGER LEUCHTEN






CRI




For high light requirements, mounting height 4.00 - 5.00 m. - Impact-resistant clear polycarbonate attachment, UV-stabilized - Large aluminium reflector for max. light output, inside in special white paint - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Unit carrier made of hot die cast aluminium, corrosion-resistent, outside painted in colour - All electrical components are arranged on a block - Adapter jack for connection -Available in any RAL or DB colour without surcharge - Please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury	vapour lamp
Nominal lamp power	50 W
Lamp flux	2000 lm
Luminous efficacy	20 lm/W
CCT	3400 K

LOR	59%
ULOR	14%
Total flux	1181 lm
Total power	59 W



1 x High pressure mercury vapour lamp Nominal lamp power 80 W Lamp flux 4000 lm

Luminous efficacy 27 lm/W CCT 3400 K CRI 54

LOR 59%
ULOR 14%
Total flux 2362 lm
Total power 89 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 17.72 in Diameter: 15.75 in Electric

System power: 59-89 W

54

Protection

IP: 55