

Product data sheet

VOLKMAR I (2-ARMED)

9.870.0190.08


LEIPZIGER LEUCHTEN



IP
55

For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant opal polyethylene attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection - Available in any RAL or DB colour without surcharge - Order pole for single-bracket luminaire, dia. 60 mm, separately - Order pole for multi-bracket luminaire, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated


Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	36 lm/W
CCT	3400 K
CRI	54

LOR	73%
ULOR	28%
Total flux	4944 lm
Total power	137 W




1 x High pressure mercury vapour lamp

Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	33 lm/W
CCT	3400 K
CRI	54

LOR	73%
ULOR	28%
Total flux	2908 lm
Total power	89 W


Light output 2



1 x High pressure mercury vapour lamp

Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	36 lm/W
CCT	3400 K
CRI	54

LOR	73%
ULOR	28%
Total flux	4944 lm
Total power	137 W



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	73%
Lamp flux	4000 lm	ULOR	28%
Luminous efficacy	33 lm/W	Total flux	2908 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.35 in

Diameter: 16.14 in

Electric

System power: 178-274 W

Protection

IP: 55