


Product data sheet


投光灯
PAK473100 PAK-L07-070A-AE-L
PAK



IP
65


高压铸铝成型外壳，5MM钢化玻璃，反射罩采用高纯阳极电镀铝，安全活页装置，四角下压式锁扣设计，安装方便；U型承托镀锌防锈支架，安装方便，可调角度，优质硅胶耐高温，防水密封圈。防护等级：IP65 适用光源：金卤灯/高压钠灯 70W 适用于建筑泛光照明、广告招牌照明、体育馆、货场、码头、车场等照明。

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	Socket	Rx7S
Lamp flux	5800 lm	LOR	66%
Luminous efficacy	47 lm/W	Total flux	3831 lm
CCT	2000 K	Total power	81.7 W
CRI	31		



1 x Metal halide lamp

Nominal lamp power	70 W	Socket	Rx7S
Lamp flux	6500 lm	LOR	66%
Luminous efficacy	53 lm/W	Total flux	4294 lm
CCT	4000 K	Total power	81.7 W
CRI	80		

Mounting mode

Pole top mounted, Floor mounted

Shape and measurements

Length: 8.00 in
Width: 12.45 in
Height: 5.46 in

Adjustability

Tiltable

Electric

System power: 81.7 W

Protection

IP: 65