Product data sheet

LUCAS XI (1-ARMED) 9.849.3066.15

LEIPZIGER LEUCHTEN









Mounting height 6.00 m. Other heights please inquire. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes reinforced and hot-galvanized triple offset Pole dia. 76 mm inclusive painted bracket made of spezial steel Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



| 1 x High pressure mercury vapour lamp | | |
|---------------------------------------|---------|--|
| Nominal lamp power | 125 W | |
| Lamp flux | 6800 lm | |
| Luminous efficacy | 42 lm/W | |
| CCT | 3400 K | |
| CRI | 54 | |
| | | |

| LOR | | 84% |
|----------|------|---------|
| Total fl | ux | 5697 lm |
| Total p | ower | 137 W |
| | | |



| 1 x High pressure mercury vapour lamp | | | | |
|---------------------------------------|---------|-------------|--|--|
| Nominal lamp power | 80 W | LOR | | |
| Lamp flux | 4000 lm | Total flux | | |
| Luminous efficacy | 38 lm/W | Total power | | |
| CCT | 3400 K | | | |
| CRI | 54 | | | |

Mounting mode

Pole top mounted

Shape and measurements

Height: 19.69 in Diameter: 22.44 in Electric

System power: 89-137 W

Protection

IP: 55

84% 3351 lm 89 W