## Product data sheet

EVA I 9.898.3142.00

LEIPZIGER LEUCHTEN








For medium light requirements, mounting height 3.00 - 5.00 m. - Impact-resistant opal polyethylene attachment - Large aluminium reflector for max. light output, underside in special white paint - Unit carrier made of die cast aluminium, corrosion-resistant, outside painted in color - All electrical components are arranged on a block - Adapter jack for connection -Available in any RAL or DB colour without surcharge - Please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated


## Light output 1



1 x High pressure mercury vapour lamp				
Nominal lamp power	50 W			
Lamp flux	2000 lm			
Luminous efficacy	28 lm/W			
CCT	3400 K			
CRI	54			

1 v High pressure mercury vanour lamp

LOR	82%
ULOR	28%
Total flux	1633 lm
Total power	59 W



1 X Flight pressure friered	ily vapour iarrip	
Nominal lamp power	80 W	
Lamp flux	4000 lm	
Luminous efficacy	37 lm/W	
CCT	3400 K	

1 X Flight pressure thereary vapour lamp				
Nominal lamp power	80 W	LOR	82%	
Lamp flux	4000 lm	ULOR	28%	
Luminous efficacy	37 lm/W	Total flux	3267 lm	
CCT	3400 K	Total power	89 W	
CRI	54			

Mounting mode

Pole top mounted

Shape and measurements

Height: 17.72 in Diameter: 15.75 in Electric

System power: 59-89 W

Protection

IP: 55