


Product data sheet

CLARA VII (WITH SHIELD ON SIDE FACING BUILDING, CLEAR ATTACHMENT)
9.767.1052.25
LEIPZIGER LEUCHTEN



For medium/high light requirements, mounting height 4.00 – 7.00 m. - Impact-resistant clear/opal polycarbonate attachment,UV- stabilized - High-pressure lamps with coated bulbs use reflector lamellae made of premium highest-grade aluminium, burnishid and anodized, for light guidance and glare limitation - Computer-optimized reflector system for high-pressure lamps with clear glass tubular bulbs ensures excellent illumination -Aluminium reflector finished in special white paint for max. light reflection - Corrosion-resistant cast aluminium unit carrier, painted - All electrical components on one block - Adapter jack connection -Available in any RAL or DB colour without surcharge - for post dia. 76mm; order post dia.76mm separately

Light output 1



1 x Metal halide lamp			
Nominal lamp power	100 W	LOR	50%
Lamp flux	10000 lm	ULOR	8%
Luminous efficacy	44 lm/W	Total flux	5044 lm
CCT	3000 K	Total power	115 W
CRI	90		

Mounting mode

Pole top mounted

Electric

System power: 115 W

Shape and measurements

Height: 27.56 in
Diameter: 29.92 in