

# Product data sheet

PURE 1 SPOT PRO CEILING  
09.2487/POWER LED 16W1225LM/29°  
FLOS



Luminaire for ceiling or three-phase electric track installation. For very low voltage halogen lamps, standard and discharge lamps or LED . Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double Teflon insulation. Aluminum body, placed above the lamp holder, black thermoplastic and 4 mm tempered glass screen-support ring. Die-cast aluminum alloy body, cover and adjustable lamp support, powder-coated white, grey or black. Thermoplastic three-phase adapter. Finishes: white (30), grey (02), black (14).

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 3200 K |
| Nominal lamp power | 16 W    | CRI         | 80     |
| Total flux         | 1225 lm | LOR         | 100%   |
| Luminous efficacy  | 77 lm/W | Total power | 16 W   |

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 1.69 in  
Width: 4.34 in  
Height: 5.31 in

## Adjustability

Free

## Electric

System power: 16 W  
Appliance Class: I

## Protection

IP: 20