

Product data sheet


投光灯
PAK473102 PAK-L07-250L-AE-LJ
PAK




IP
65

高压铸铝成型外壳，5MM钢化玻璃，反射罩采用高纯阳极电镀铝，安全活页装置，四角下压式锁扣设计，安装方便；U型承托镀锌防锈支架，安装方便，可调角度，优质硅胶耐高温，防水密封圈。防护等级：IP65 适用光源：金卤灯 250W 适用于建筑泛光照明、广告招牌照明、体育馆、货场、码头、车场等照明。

Light output 1



1 x Metal halide lamp			
Nominal lamp power	250 W	Socket	E40
Lamp flux	22700 lm	LOR	68%
Luminous efficacy	57 lm/W	Total flux	15337 lm
CCT	4000 K	Total power	269 W
CRI	65		



1 x Metal halide lamp			
Nominal lamp power	250 W	Socket	E40
Lamp flux	24200 lm	LOR	68%
Luminous efficacy	61 lm/W	Total flux	16350 lm
CCT	4000 K	Total power	269 W
CRI	70		

Mounting mode

Pole top mounted, Floor mounted

Shape and measurements

Length: 9.88 in
Width: 17.68 in
Height: 6.75 in

Adjustability

Tiltable

Electric

System power: 269 W

Protection

IP: 65