


# Product data sheet

RADIIS 210 Ø280 ZOOM / FL 26 GR, LED 36W/4000K  
5747828582  
LOUIS POULSEN



Radiis 210 Concept: The fixture emits even, channelled light. Three types of light systems – zoom, lens and wall washer – together with direction adjustment options and colour and light filters, make it possible to illuminate buildings, vegetation, signs, etc. in an effective and interesting way, while promoting a sense of security. Finish: Glass, stainless steel. Material: Housing: Injection moulded anodised aluminium. Top ring: Brushed stainless steel, 316L. Glass: Extra clear, hardened glass. Driver box: Synthetic. Installation sleeve: Synthetic. Mounting: An installation sleeve must be used (ordered separately). The IP68 driver box/connection box is pre-mounted with sealed wiring and IP68 connectors. The connecting cable terminates with an IP68 connector (supplied) for cable type H07RN-F Ø7-12mm (2x2.5mm<sup>2</sup>). Looping: Yes. Certified to withstand load of up to 2,000 kg. Weight: Max. 6kg. Class: Ingress protection IP66, IP67, IP68, IP69K. IK10. Electric shock protection II wo. ground.

## Light output 1



1 x LED			
Nominal lamp power	36 W	LOR	48%
Lamp flux	3549 lm	ULOR	48%
Luminous efficacy	48 lm/W	Total flux	1714 lm
CCT	4000 K	Total power	36 W
CRI	80		

## Mounting mode

Floor recessed

## Shape and measurements

Height: 0.39 in

Diameter: 11.02 in

## Adjustability

Tiltable

## Electric

System power: 36 W

Appliance Class: II

## Protection

IP: 67