


# Product data sheet

GUSTAV I (W. SHIELD ON SIDE FACING BUILDING)  
9.681.3142.27  
LEIPZIGER LEUCHTEN




Mounting height of 3.00 to 4.50 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge - Order pole, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



### 1 x High pressure mercury vapour lamp

|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 50 W    | LOR         | 50%    |
| Lamp flux          | 2000 lm | ULOR        | 10%    |
| Luminous efficacy  | 17 lm/W | Total flux  | 991 lm |
| CCT                | 3400 K  | Total power | 59 W   |
| CRI                | 54      |             |        |



### 1 x High pressure mercury vapour lamp

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 80 W    | LOR         | 50%     |
| Lamp flux          | 4000 lm | ULOR        | 10%     |
| Luminous efficacy  | 22 lm/W | Total flux  | 1982 lm |
| CCT                | 3400 K  | Total power | 89 W    |
| CRI                | 54      |             |         |

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 29.13 in

Diameter: 9.84 in

## Design

Material impression: Matt

Color of housing: White

## Electric

System power: 59-89 W

Ballast: ECG

## Integrated sensors

Integrated sensors: Motion sensor

## Protection

IP: 55

Designation labels: CE

#### Other operating numbers

Ambient temperature range: -13...95°F