## Product data sheet

LUCAS I (1-ARMED) 9.851.3162.15

LEIPZIGER LEUCHTEN









Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire, Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



$1\ x$ High pressure mercury vapour lamp		
Nominal lamp power	125 W	
Lamp flux	6800 lm	
Luminous efficacy	42 lm/W	
CCT	3400 K	
CRI	54	

LOR	84%
Total flux	5697 lm
Total power	137 W



1 x High pressure mercury vapour lamp			
Nominal lamp power	80 W	LOR	
Lamp flux	4000 lm	Total flux	
Luminous efficacy	38 lm/W	Total power	
CCT	3400 K		
CRI	54		

Mounting mode Electric

Pole top mounted System power: 89-137 W

2,000

Shape and measurements Protection
Height: 19.69 in IP: 55

Created by luminaires.dialux.com (4 May, 2024)

Diameter: 22.44 in

84% 3351 lm

89 W