

# Product data sheet


KORA V (1-ARMED)  
9.107.1132.05  
LEIPZIGER LEUCHTEN



IP  
55

One or double-bracket pole luminaire with intensive brightness (height 4.50 and 6.00 m) in order to illuminate streets and footpaths. - Attachment made of plexiglass XT, sandblasted on one side - Computer-optimized reflector systems for high-pressure lamps with clear glass tubular bulbs/DULUX lamps ensures excellent illumination - Special steel luminaire body and unit carrier, available painted in any RAL or DB colour without surcharge, or ground and passivated - Luminaire case fold out for lamp change - Adapter jack connection - Included pole door to take in a cable joint box - Scope of supply includes square pole, incl. special steel bracket and electrical supply element (intermediate unit, ignition unit, condenser) - Available for 3 fastening variants in the ground: flange sheet, flange sheet in order to pave over, or end piece, situated at the pole, to set in the ground Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



<b>1 x Metal halide lamp</b>			
Nominal lamp power	70 W	LOR	61%
Lamp flux	7200 lm	Total flux	4414 lm
Luminous efficacy	50 lm/W	Total power	88 W
CCT	3000 K		
CRI	90		

## Mounting mode

Pole integrated

## Electric

System power: 88 W

## Shape and measurements

Length: 31.50 in  
Width: 9.84 in  
Height: 3.15 in

## Protection

IP: 55