


Product data sheet

MEGA TUBE
611875.004
RZB




IP
65

IK
05

Series: MEGA TUBE Attractive cylindrical bollard with innovative housing design and high-quality LED optics. Luminaire tube Ø 115 mm made of corrosion-resistant aluminium profile, powder coated. Recessed stainless steel fixing plate. With membrane valve as a standard to avoid condensed water. Non-corrosive gear compartment made of mould-cast dual compound thermoplastic with integral TP gasket. Opal glass: mouth-blown, satin finish. The robust stainless steel mounting base ensures long-term stability. Elongated holes in the base for subsequent and simple alignment of the luminaire. Connection box on base, max. 2 x 3 x 2.5 mm² for through wiring. Colour: silver, matt (approx. RAL 9006) Diameter: 115 mm Height: 600 mm Lamp: QA60 (clear) System power: 60 W Rated luminous flux: 570 lm Luminous efficiency: 10 lm/W Control gear: Converter not necessary Protection class: I Type of protection: IP 65

Light output 1



1 x Halogen low voltage lamp without reflector

Nominal lamp power	57 W	Socket	E27
Lamp flux	915 lm	LOR	79%
Luminous efficacy	13 lm/W	ULOR	45%
CCT	3000 K	Total flux	727 lm
CRI	90	Total power	57 W

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Height: 23.62 in
Diameter: 4.53 in

Adjustability

Fixed

Electric

System power: 57 W

Protection

IP: 65
IK: 05