Product data sheet


NADJA III (1-ARMED) 9.876.2152.05 LEIPZIGER LEUCHTEN





Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium,burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	50 W	LOR	78%
Lamp flux	3500 lm	Total flux	2737 lm
Luminous efficacy	44 lm/W	Total power	62 W
CCT	2000 K		
CRI	25		

4	A A	ŚЩ	X	7-	7
	H			4	1
K	X		X	X	\Box
	\sim	\square	H	\succ	D)
$\left \right>$			P	V	X
\bigcirc	\bigtriangledown		t		
\mathcal{A}			7		X
1			-		X

1 x High pressure sodium vapour lamp	
--------------------------------------	--

Nominal lamp power	70 W	LOR	78%
Lamp flux	5600 lm	Total flux	4379 lm
Luminous efficacy	53 lm/W	Total power	83 W
CCT	2000 K		
CRI	25		

Mounting mode	Electric
Pole top mounted	System power: 62-83 W
Shape and measurements	Protection
Height: 16.54 in	IP: 55
Diameter: 16.54 in	