## Product data sheet

VOLKMAR II (WALL FITTING) 9.840.0087.05 LEIPZIGER LEUCHTEN






CRI

For medium light requirements, mounting heights from 3.00 - 4.00 m. - Luminaire body made of aluminium/galvanized steel sheet - Impactresistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB -colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure sodium vapour lamp						
Nominal lamp power	100 W	LOR				
Lamp flux	10400 lm	ULOR				
Luminous efficacy	77 lm/W	Total flux				
CCT	2000 K	Total power				

25

$(/XX \square XX)$
$(/ X X \square X X)$
$/// \times \times$
CALLY VIIIV Y LAN
$\vee \setminus \land \land \land \top \land \land \land \lor \lor$
$X \setminus N \top V / X$

1 x High pressure sodium vapour lamp
--------------------------------------

Nominal lamp power	70 W	LOR	85%
Lamp flux	5600 lm	ULOR	28%
Luminous efficacy	57 lm/W	Total flux	4739 lm
CCT	2000 K	Total power	83 W
CRI	25		
ССТ	2000 K		

Wall mounted

## Shape and measurements

Height: 16.14 in Diameter: 16.14 in Electric System power: 83-115 W Protection

IP: 55

85% 28% 8802 lm

115 W