Product data sheet

SONIS EVO 672251.002

RZB








Item Number: 672251.002 Series: Sonis EVO Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing and cover made of powder-coated sheet steel, anti-glare screen made of plastic (ABS) metallised, highly polished, for grid ceilings (600x600mm). With single battery system in combined non-maintained power mode, with integrated self-test system and status display on the luminaire. Lamp (LED) included. Available Colours: white Type of Installation: Recessed ceiling mounting Dimensions: L 597, B 597, H 1, HE 37, HEL 34mm Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Rated Operating Time: 3h Emergency Lighting System: automatic self-test Safety Marks: F-mark Luminaire flux LED: 3400lm System power: 33W Beam Angle: 78°/74° Unified Glare Ratio: 18,3 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	30 W	CRI	80
Total flux	3400 lm	LOR	100%
Luminous efficacy	113 lm/W	Total power	30 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.50 in Width: 23.50 in Height: 0.04 in

Adjustability

Fixed

Electric

System power: 30 W

Protection

IP: 20