Product data sheet

VOLKMAR III (WALL FITTING) 9.840.0080.00

LEIPZIGER LEUCHTEN









For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury	vapour lamp
Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	27 lm/W
CCT	3400 K
CRI	54

LOR	55%
ULOR	15%
Total flux	3714 lm
Total power	137 W



i x High pressure mercur	y vapour iamp
Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	25 lm/W
CCT	3400 K
CRI	54

LOR	55%
ULOR	15%
Total flux	2185 lm
Total power	89 W

Mounting mode

Wall mounted

Shape and measurements

Length: 56.61 in Width: 2.60 in Height: 2.72 in Electric

System power: 89-137 W

Protection

IP: 55