


Product data sheet

RICHARD IV (W. SHIELD ON SIDE FACING BUILDING)
9.892.1052.35
LEIPZIGER LEUCHTEN



Mounting height approx. 3.00 - 4.50 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Circular shield for glare limitation made of anodized aluminium - Large aluminium reflector, inside finished in special white paint for max. light reflection - Aluminium cover, painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge - Order pole, dia. 60 mm, separately Order pole for double-bracket luminaire, dia. 76 mm, separately

Light output 1



1 x Metal halide lamp			
Nominal lamp power	100 W	LOR	51%
Lamp flux	10000 lm	ULOR	11%
Luminous efficacy	44 lm/W	Total flux	5115 lm
CCT	3000 K	Total power	115 W
CRI	90		

Mounting mode

Pole top mounted

Electric

System power: 115 W

Shape and measurements

Height: 19.88 in
Diameter: 7.87 in