## Product data sheet

NADJA II (WALL FITTING) 9.845.2152.05


LEIPZIGER LEUCHTEN





Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vap	our lamp
------------------------------	----------

5 1			
Nominal lamp power	50 W	LOR	77%
Lamp flux	3500 lm	Total flux	2701 lm
Luminous efficacy	44 lm/W	Total power	62 W
CCT	2000 K		
CRI	25		

	11A
X+	-12
$\mathcal{A} \mathcal{P}$	$\exists$

1 x High	pressure sodium vapour la	amp

<b>U</b> .			
Nominal lamp power	70 W	LOR	77%
Lamp flux	5600 lm	Total flux	4321 lm
Luminous efficacy	52 lm/W	Total power	83 W
CCT	2000 K		
CRI	25		

Mounting mode	Electric
Wall mounted	System power: 62-83 W
Shape and measurements	Protection
Height: 20.08 in	IP: 55
Diameter: 20.08 in	