Product data sheet

VOLKMAR II (1-ARMED) 9.870.0187.05

LEIPZIGER LEUCHTEN









For medium light requirements, mounting heights from 3.00 - 4.00 m. - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL - or DB -colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm, separately -Order pole for multi-bracket luminaire, dia. 76 mm,separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure sodium vapour lamp				
Nominal lamp power	50 W			
Lamp flux	3500 lm			
Luminous efficacy	48 lm/W			
CCT	2000 K			
CRI	25			

LOR	85%
ULOR	28%
Total flux	2962 lm
Total power	62 W



1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	85%
Lamp flux	5600 lm	ULOR	28%
Luminous efficacy	57 lm/W	Total flux	4739 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.35 in Diameter: 16.14 in Electric

System power: 62-83 W

Protection

IP: 55