## Product data sheet

LUCAS VI (1-ARMED BEADED) 9.856.2032.16

LEIPZIGER LEUCHTEN








High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately, inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



i x High pressure sodium	vapour iamp
Nominal lamp power	70 W
Lamp flux	5600 lm
	ГС I (\A)

Luminous efficacy 56 lm/W CCT 2000 K CRI 25

LOR 83%
ULOR 2%
Total flux 4642 lm
Total power 83 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 19.69 in Diameter: 22.44 in Electric

System power: 83 W

Protection

IP: 55