


# Product data sheet

LUCAS II (1-ARMED)  
9.852.3066.15  
LEIPZIGER LEUCHTEN



Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire, Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	42 lm/W
CCT	3400 K
CRI	54

LOR	84%
Total flux	5697 lm
Total power	137 W



### 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	38 lm/W
CCT	3400 K
CRI	54

LOR	84%
Total flux	3351 lm
Total power	89 W

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 19.69 in

Diameter: 22.44 in

## Design

Material impression: Matt

Color of housing: White

## Electric

System power: 89-137 W

Ballast: ECG

## Protection

IP: 55

Designation labels: CE

## Other operating numbers

Ambient temperature range: -4...95°F