Product data sheet

NADJA V (1-ARMED) 9.870.1072.85

LEIPZIGER LEUCHTEN








Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x Metal halide lamp
Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

150 W
15000 lm
68 lm/W
2900 K
90

LOR	77%
Total flux	11575 lm
Total power	170 W

Mounting mode

Pole top mounted, Ceiling mounted

Shape and measurements

Height: 20.08 in Diameter: 20.08 in

Design

Material impression: Matt Color of housing: Black

Glare protection

Glare protection: UGR < 19

Electric

System power: 170 W

Ballast: ECG Controller: DALI

Protection

IP: 55

Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: 32...95°F