


Product data sheet

MINIFRANCO
160114
FLOS



Outdoor luminaire for installation on wall or on pole. Configuration: die-cast aluminium structure. EN AB-47100 (low copper content) Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Pure aluminium optics, tempered extra-clear glass diffuser, silicone gaskets.

Light output 1



1 x Halogen low voltage lamp without reflector

Nominal lamp power	60 W	Socket	E27
Lamp flux	820 lm	LOR	62%
Luminous efficacy	8 lm/W	Total flux	510 lm
CCT	2800 K	Total power	60 W
CRI	100		

Mounting mode

Wall mounted, Pole top mounted

Shape and measurements

Length: 6.89 in
Width: 4.17 in
Height: 9.65 in

Adjustability

Tiltable

Electric

System power: 60 W
Appliance Class: I

Protection

IP: 65
IK: 07