Product data sheet

NADJA IV (WALL FITTING) 9.847.3142.05

LEIPZIGER LEUCHTEN









Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury	vapour lamp
Nominal lamp power	50 W
Lamp flux	2000 lm
Luminous efficacy	27 lm/W
CCT	3400 K
CRI	54

LOR	78%
Total flux	1564 lm
Total power	59 W



I x High pressure mercury	vapour lamp
Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	35 lm/W
CCT	3400 k
CRI	54

LOR	78%
Total flux	3128 lm
Total power	89 W

Mounting mode

Wall mounted

Shape and measurements

Height: 16.54 in Diameter: 16.54 in Electric

System power: 59-89 W

Protection

IP: 55