


Product data sheet

PH 80 E27 LED 2700K 18W
5744610816
LOUIS POULSEN



PH 80 Design : Poul Henningsen Concept : The fixture emits diffuse and symmetrical light. The majority of the light is directed downwards, and the opal acrylic shades provide comfortable room lighting. The red hue of the top reflector helps giving the light a warmer glow. Finish : White opal acrylic. High lustre chrome plated. Material : Shades: High pressure moulded white opal acrylic. Top shade: Black, high pressure moulded polycarbonate. Base: Black, high pressure moulded ABS. Stem: High lustre chrome plated, steel. Mounting : Cable type: Plastic cord with plug. Cable length: 2.6m. Light control: On/off switch on cord. Class : Ingress protection IP20. Electric shock protection II w/o ground. Weight : Max. 7.5kg.

Light output 1



1 x LED			
Nominal lamp power	18 W	LOR	57%
Lamp flux	2000 lm	ULOR	13%
Luminous efficacy	63 lm/W	Total flux	1143 lm
CCT	2700 K	Total power	18 W
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Height: 51.77 in

Diameter: 21.65 in

Adjustability

Fixed

Electric

System power: 18 W

Appliance Class: II

Protection

IP: 20