## Product data sheet

NADJA I (1-ARMED) 9.870.2036.05

LEIPZIGER LEUCHTEN









Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 x High pressure sodium vapour lamp		
Nominal lamp power	50 W	
Lamp flux	3500 lm	
Luminous efficacy	44 lm/W	
CCT	2000 K	
CRI	25	

LOR	77%
Total flux	2701 lm
Total power	62 W



1 x High pressure sodium vapour lamp			
Nominal lamp power	70 W	LOR	
Lamp flux	5600 lm	Total flux	
Luminous efficacy	52 lm/W	Total power	
CCT	2000 K		
CRI	25		

Mounting mode

Pole top mounted

Shape and measurements

Height: 20.08 in Diameter: 20.08 in Electric

System power: 62-83 W

Protection

IP: 55

77% 4321 lm 83 W