


# Product data sheet

PH 6½-6 LED 2700K 96W  
5741094943  
LOUIS POULSEN



PH 5-4½ & PH 6½-6 Design : Poul Henningsen Concept : The trumpet-shaped top shade on the fixture provides illumination of the area above the three shades, which primarily direct the light downwards. A base reflector and a blue glare ring protect against glare from all angles. The strongest light is directly under the fixture. The shades have a matte white painted finish to ensure very comfortable lighting. Finish : White. Material : Shades: Spun aluminium. Anti-glare disc: Blue, spun aluminium. Struts: Rolled aluminium coloured. Mounting : Suspension type: Cable 3x0,75mm² or cable 3x0,75mm² & wire. Canopy: Yes. Cable length: PH 5-4½: 3m, PH 6½-6: 4m. Class : Ingress protection IP20. Electric shock protection I w. ground. Weight : Max. 6kg.

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 2700 K |
| Nominal lamp power | 96 W    | CRI         | 90     |
| Total flux         | 4684 lm | LOR         | 100%   |
| Luminous efficacy  | 49 lm/W | ULOR        | 10%    |
|                    |         | Total power | 96 W   |

## Mounting mode

Pendant

## Shape and measurements

Height: 12.52 in

Diameter: 18.35 in

## Adjustability

Fixed

## Electric

System power: 96 W

Appliance Class: I

## Protection

IP: 20