Product data sheet

NADJA I (WALL FITTING BEADED) 9.840.1072.06


LEIPZIGER LEUCHTEN



Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

IP 55

Light output 1



| 1 x Metal halide lamp | | | |
|-----------------------|----------|-------------|----------|
| Nominal lamp power | 150 W | LOR | 78% |
| Lamp flux | 15000 lm | Total flux | 11695 lm |
| Luminous efficacy | 69 lm/W | Total power | 170 W |
| CCT | 2900 K | | |
| CRI | 90 | | |
| | | | |

Mounting mode

Wall mounted Shape and measurements Height: 20.08 in Diameter: 20.08 in Electric

System power: 170 W

Protection IP: 55