

Product data sheet


EVA III
9.751.3142.00
LEIPZIGER LEUCHTEN



IP
55


For medium light requirements, mounting height 4.50 - 6.00 m. - Impact-resistant beaded polycarbonate attachment, UV-stabilized - Aluminium reflector finished in special white paint for max. light reflection - Corrosion-resistant cast aluminium unit carrier, painted - All electrical components on a block - Adapter jack for connection - Available in any RAL- or DB -colour without surcharge - For concrete pole with flange plate made of hot galvanized steel Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	50 W	LOR	83%
Lamp flux	2000 lm	ULOR	22%
Luminous efficacy	28 lm/W	Total flux	1668 lm
CCT	3400 K	Total power	59 W
CRI	54		



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	83%
Lamp flux	4000 lm	ULOR	22%
Luminous efficacy	37 lm/W	Total flux	3337 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Pole top mounted

Shape and measurements

Height: 17.72 in
Diameter: 15.75 in

Electric

System power: 59-89 W

Protection

IP: 55