
Product data sheet

LUCAS X (WALL FITTING BEADED) 9.833.3142.16



Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


Light output 1



1 x High pressure mercury vapour l	amp

IP 55

50 W	LOR	83%
2000 lm	ULOR	2%
28 lm/W	Total flux	1658 lm
3400 K	Total power	59 W
54		
	2000 lm 28 lm/W 3400 K	2000 lmULOR28 lm/WTotal flux3400 KTotal power



1 x High pressure mercury vapour lamp					
Nominal lamp power	80 W	LOR	83%		
Lamp flux	4000 lm	ULOR	2%		
Luminous efficacy	37 lm/W	Total flux	3316 lm		
CCT	3400 K	Total power	89 W		
CRI	54				

Mounting mode Wall mounted Shape and measurements

Height: 22.44 in Diameter: 22.44 in

Electric

System power: 59-89 W

Protection

IP: 55