


# Product data sheet

ALPHABET FOCUS RECESSED LUMINAIRE, RECESSED ADJUSTABLE SPOTLIGHT  
AF1104108-31-30\_(ALPHA-MIN)  
SCHMITZ | WILA



alphabet focus LED 3000 K Recessed Luminaire, Light distribution direct Recessed Adjustable Spotlight Product: AF1104108-31-30 Operating technology: independent driver required Light Technique highly precise lens technology (PLT) for beam angles, with focus unit for stepless fine adjustment Light module 361° rotatable, with integrated rotation stop tilt range from 0-40° variable beam angles 24° - 40° CRI > 90 constant colour temperature 3000 K lifetime 50.000 h (L70) Aluminium reflector (Al99.98), high- polished Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised ring thickness of only 2 mm for homogeneous appearance in the ceiling ring colour white, RAL 9016 Operating and assembly technology LED driver to be ordered separately Driver suitable for connection to central battery systems Quick installation due to 3-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 36 W Colour Rendering Index: 90 Colour Temperature: 3000 K Luminaire Luminous Flux: 870 Llm - 1780 Llm System Efficiency: 46 Llm/W Half-peak Divergence  $\alpha$ : 24° - 40° Number Luminaires LZ: 0.14 - 0.07 Connector: Screw Connector, 3 x 1.5 mm<sup>2</sup> Reflector Size: R15 Diameter D: 172 mm Cut-out CO: 165 mm Installation Depth RD: 160 mm Total Weight: 1.5 kg Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record AF1104108-31-30\_(Alpha-MIN)

## Light output 1



### 1 x General service incandescent lamp

Nominal lamp power	39 W	LOR	100%
Lamp flux	870 lm	Total flux	870 lm
Luminous efficacy	22 lm/W	Total power	39 W
CCT	3000 K		
CRI	90		

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 6.30 in  
Diameter: 6.77 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 39 W  
Appliance Class: II

## Protection

IP: 20