


Product data sheet

NORA VII (1-ARMED BEADED)
9.777.3046.06
LEIPZIGER LEUCHTEN




For medium light requirements, mounting height 3.50 - 4.00 m. - Impact-resistant clear or beaded polycarbonate attachment, UV-stabilized - Special reflector of premium highest-grade aluminium, burnished and anodized, for excellent illumination and glare protection - Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection - Available in any RAL or DB colour without surcharge - Scope of delivery includes special steel post/wall-mounted bracket, painted -Order post dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp	
Nominal lamp power	50 W
Lamp flux	2000 lm
Luminous efficacy	25 lm/W
CCT	3400 K
CRI	54

LOR	73%
ULOR	3%
Total flux	1464 lm
Total power	59 W



1 x High pressure mercury vapour lamp	
Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	33 lm/W
CCT	3400 K
CRI	54

LOR	73%
ULOR	3%
Total flux	2927 lm
Total power	89 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 11.81 in
Diameter: 21.26 in

Electric

System power: 59-89 W

Protection

IP: 55
Designation labels: CE, ENEC, F