



Product data sheet

CENTRYXX IP65
672170.002.1
RZB




Series: CENTRYXX IP65 Flat, square surface-mounted luminaire. Base: die-cast aluminium, powder-coated Cover: polycarbonate. With plastic lenses for area lighting. Electronic ballast included. Self-contained system with automatic self-test. Luminaires with limited surface temperature in accordance with EN 60598-2-24; for use in environments in which a deposit of conductive dust on the luminaire can be expected. Ball impact proof in accordance with DIN 18032-3. Qualified for use in the food and drink industry. Colour: white Length: 198 mm Width: 198 mm Height: 38 mm Weight: 1.03 kg Operating mode: maintained power mode Duration time: 3 h Lamp: LED Socket: without socket Colour temperature: 6500K Colour rendering index (CRI): 70 System power: 6.5 W Rated luminous flux: 440 lm Luminous flux, emergency: 360 lm System power, emergency: 0 W Control gear: Regulated power supply Protection class: I Type of protection: IP65

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	6.5 W	CRI	70
Total flux	360 lm	LOR	100%
Luminous efficacy	55 lm/W	Total power	6.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	6500 K
Nominal lamp power	6.5 W	CRI	70
Total flux	440 lm	LOR	100%
Luminous efficacy	68 lm/W	Total power	6.5 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 7.80 in
Width: 7.80 in
Height: 1.50 in

Electric

System power: 13 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Adjustability

Fixed

Protection

IP: 65

IK: 08