


# Product data sheet

LEO 160 ON POST  
1233548 ON POST  
FLOS



Outdoor luminaire for installation on wall or on post. Configuration: die-cast aluminium structure . EN AB-47100 (low copper content). Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Sandblasted glass.

## Light output 1



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	G12
Lamp flux	3300 lm	LOR	35%
Luminous efficacy	33 lm/W	ULOR	17%
CCT	3000 K	Total flux	1149 lm
CRI	81	Total power	35 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 6.30 in  
Width: 6.30 in  
Height: 8.66 in

## Adjustability

Fixed

## Electric

System power: 35 W  
Appliance Class: I

## Protection

IP: 65  
IK: 05