Product data sheet


MAXIMARTINA AQUA LED 105211145 FLOS





• Outdoor round spotlight • Configuration: Turned and anodized or painted aluminium structure with stainless steel adjustable bracket • Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Tempered transparent glass with silkscreen border, nitrile rubber gaskets. • Glass fixed to the structure through a robotic gluing system.

Light output 1



1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI

15.3 W 723 lm 49 lm/W 4000 K 80 LOR Total flux Total power

99% 713 lm 14.7 W

Mounting mode	Electric
Wall mounted	System power: 14.7 W
Shape and measurements	Appliance Class: III
Height: 2.20 in	Protection
Diameter: 4.65 in	IP: 68
Adjustability	IK: 07

Tiltable