



# Product data sheet

ARLINE  
741704.003.1  
RZB



Series: Arline Type of Protection: IP 20 Protection Class: II Voltage: 230 V / 50 Hz Housing: die-cast aluminium, powder-coated. Projector 360° horizontally rotatable. Gimbals can be tilted +/- 30° in any direction. Luminaire head 90° vertically inclinable. With multi adaptor for 230 V 3-circuit tracks. LED included. Available Colours: jet black (RAL 9005) Type of Installation: Track on ceiling Dimensions: L 260, B 180, H 175 Lamp: LED AR111 Colour Temperature: 4000K Socket 1: G53 Operating Mode Lamp 1: Converter dimmable using leading or trailing edge dimmer Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) System power: 26W Beam Angle: 40° Number of fittings B10A: 30 Number of fittings B16A: 48 Number of fittings C10A: 30 Number of fittings C16A: 48 Inrush current: 2,5A Unified Glare Ratio: 17,6 EEC: A - AA

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	26 W	CRI	80
Total flux	2500 lm	LOR	100%
Luminous efficacy	96 lm/W	Total power	26 W

## Mounting mode

Ceiling mounted

## Electric

System power: 26 W

## Shape and measurements

Length: 7.09 in

Width: 10.24 in

Height: 6.89 in

## Protection

IP: 20

IK: 03

## Adjustability

Rotatable, Tilttable

## Design

Color of housing: Black