Product data sheet

MORITZ F VIII (1-ARMED) 9.213.1082.01

LEIPZIGER LEUCHTEN








Universal luminaire for mounting heights of 8.00 m to 16.00 m for different applications with high light requirements - Luminaire made of cast aluminium, varnished - Superior lighting due to asymmetrical and symmetrical, resp., luminous intensity distribution - Cover of single-pane safety glass, hinged - Cable protection braided hosing and closures made of stainless steel - All electrical parts fitted - Available in any required RAL or DB colour without extra price - Pole mounting, hot-dip galvanised and varnished, is part of the delivery - Please order separately: conical pole for Ø 76 mm pole end Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x Metal halide lamp	
Nominal lamp power	250 W
Lamp flux	22000 lm
Luminous efficacy	62 lm/W
CCT	3200 K
CRI	80

LOR	78%
Total flux	17142 lm
Total power	275 W
Total power	275 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 21.26 in Width: 21.26 in Height: 6.89 in

Adjustability

Height adjustable

Electric

System power: 275 W

Protection

IP: 65