


Product data sheet

ROBERT III (1-ARMED BEADED)
9.863.5507.06
LEIPZIGER LEUCHTEN



Mounting height 4,50 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in color - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - scope of supply includes hot galvanized and painted offset pole, dia. 102 mm, and bracket

Light output 1



2 x Compact fluorescent lamp

Nominal lamp power	26 W	LOR	80%
Lamp flux	1800 lm	Total flux	2889 lm
Luminous efficacy	52 lm/W	Total power	56 W
CCT	2899 K		
CRI	90		

Mounting mode

Pole integrated, Ceiling mounted

Shape and measurements

Height: 11.81 in
Diameter: 23.62 in

Design

Material impression: Matt
Color of housing: White

Electric

System power: 56 W
Ballast: ECG
Controller: DALI
Suitable for feed-through wiring

Protection

Designation labels: CE

Other operating numbers

Ambient temperature range: -13...95°F