

Product data sheet

HOME 203
611976.0031
RZB



IP
54

IK
06

Series: Home 203 Type of Protection: IP 54 Protection Class: I Voltage: 200 - 240 V / 50 - 60 Hz Bollard for socket mounting. Housing: pressure die-cast aluminium, powder-coated. Diffuser: plastic (polycarbonate), opal. Driver included. LED included. Available Colours: anthracite metallic Type of Installation: ground installation Dimensions: L 40, B 120, H 650 Lamp: LED Life time: 25000 h (L70/B50) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK06 (1 Joule) Luminaire flux LED: 290lm System power: 9W Beam Angle: 112°/180° Number of fittings B10A: 110 Number of fittings B16A: 180 Inrush current: 25A Unified Glare Ratio: 32,9 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9 W	CRI	80
Total flux	290 lm	LOR	100%
Luminous efficacy	32 lm/W	Total power	9 W

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Length: 4.72 in

Width: 1.57 in

Height: 25.59 in

Adjustability

Fixed

Electric

System power: 9 W

Protection

IP: 54

IK: 06