
## Product data sheet

DIETER II (WALL FITTING) 9.839.2152.05 LEIPZIGER LEUCHTEN



Recommended mounting height 4.00 - 5.00 m. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Special steel frame, painted -Large aluminium reflector, underside finished in special white paint for max. light reflection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - All electrical components on one block - Adapter jack connection - Lamps are easy to change -Available in any RAL or DB color without surcharge Voltage: 230V 50Hz Protected to: IP 65 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated


Light output 1



1 x High pressure sodium vapour lar	np
-------------------------------------	----

IP 65

• •			
Nominal lamp power	50 W	LOR	52%
Lamp flux	3500 lm	ULOR	13%
Luminous efficacy	29 lm/W	Total flux	1811 lm
CCT	2000 K	Total power	62 W
CRI	25		



T X High pressure socium vapour lamp	igh pressure sodium vapour la	mp
--------------------------------------	-------------------------------	----

Nominal lamp power	70 W	LOR	52%
Lamp flux	5600 lm	ULOR	13%
Luminous efficacy	35 lm/W	Total flux	2898 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode
Wall mounted
Shape and measurements
Height: 10.63 in

Diameter: 10.63 in

## Electric

System power: 62-83 W

## Protection

IP: 65