


Product data sheet

RICHARD IV (1-ARMED)
9.892.1052.15
LEIPZIGER LEUCHTEN



Mounting height approx. 3.00 - 4.50 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Circular shield for glare limitation made of anodized aluminium - Large aluminium reflector, inside finished in special white paint for max. light reflection - Aluminium cover, painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge - Order pole, dia. 60 mm, separately Order pole for double-bracket luminaire, dia. 76 mm, separately

Light output 1



| | | | |
|-----------------------|----------|-------------|---------|
| 1 x Metal halide lamp | | | |
| Nominal lamp power | 100 W | LOR | 55% |
| Lamp flux | 10000 lm | ULOR | 13% |
| Luminous efficacy | 48 lm/W | Total flux | 5530 lm |
| CCT | 3000 K | Total power | 115 W |
| CRI | 90 | | |

Mounting mode

Pole top mounted

Electric

System power: 115 W

Shape and measurements

Height: 19.88 in
Diameter: 7.87 in