


# Product data sheet

EMMA70  
1163321  
FLOS



• Outdoor luminaire for installation on wall. • Configuration: die-cast aluminium structure. EN AB-47100 alloy (low copper content). • Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Tempered transparent glass, silicone gaskets.

## Light output 1



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	35 W	Socket	Gu5.3
Lamp flux	2200 lm	LOR	78%
Luminous efficacy	49 lm/W	Total flux	1709 lm
CCT	3000 K	Total power	35 W
CRI	100		

## Mounting mode

Wall mounted

## Shape and measurements

Height: 2.76 in  
Diameter: 2.76 in

## Adjustability

Fixed

## Electric

System power: 35 W  
Appliance Class: II

## Protection

IP: 65  
IK: 06