
Product data sheet

LUCAS IX (WALL FITTING BEADED) 9.831.2152.16 LEIPZIGER LEUCHTEN




Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



Nominal lamp power	50 W	LOR	80%
Lamp flux	3500 lm	ULOR	4%
Luminous efficacy	45 lm/W	Total flux	2799 lm
CCT	2000 K	Total power	62 W
CRI	25		



1 x Hiah	pressure sodium	vapour	lamp
1 X Lugu	precoure oculariti	rapour	ion ip

51			
Nominal lamp power	70 W	LOR	80%
Lamp flux	5600 lm	ULOR	4%
Luminous efficacy	54 lm/W	Total flux	4479 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode	
Wall mounted	
Shape and measurements	

Height: 22.44 in Diameter: 22.44 in

Electric

System power: 62-83 W

Protection

IP: 55