Product data sheet

LOUIS I (WALL FITTING) 9.745.2056.07 LEIPZIGER LEUCHTEN






CCT CRI

Mounting height of 3.00 to 4.50 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



| ~~ | - | | | ~ |
|-------------------|----|----------------|--------------|---|
| $\langle \rangle$ | Ŧ | \overline{A} | \mathbf{x} | S |
| 1Å | XŦ | \mathbb{R} | Ĥ | Ă |
| | | | X | + |
| H | A | \mathbf{X} | X | 7 |
| XŠ | Æ | Ð | Ž | |

| 1 x High pressure sodium vapour lamp | | | | | | |
|--------------------------------------|----------|------------|--|--|--|--|
| Nominal lamp power | 100 W | LOR | | | | |
| Lamp flux | 10400 lm | ULOR | | | | |
| Luminous efficacy | 51 lm/W | Total flux | | | | |

| 10400 lm | ULOR | 14% |
|----------|-------------|---------|
| 51 lm/W | Total flux | 5815 lm |
| 2000 K | Total power | 115 W |
| 25 | | |

| 1 x High pressure sodium vapour lamp | | | | | |
|--------------------------------------|---------|-------------|---------|--|--|
| Nominal lamp power | 70 W | LOR | 56% | | |
| Lamp flux | 5600 lm | ULOR | 14% | | |
| Luminous efficacy | 38 lm/W | Total flux | 3131 lm | | |
| CCT | 2000 K | Total power | 83 W | | |
| CRI | 25 | | | | |
| | | | | | |

Mounting mode Wall mounted

Shape and measurements

Height: 7.87 in Diameter: 7.87 in

Electric

System power: 83-115 W

Protection

IP: 55

56%